

PALFINGER P 370 KS

**THE BEST OF
TWO WORLDS**



LIFETIME EXCELLENCE




PRODUCT HIGHLIGHTS

- Robust, 2m wider aluminium workman basket with 500kg load capacity and integrated Powerlift support
- Flat sub-construction under the cage enabling best possible target reach
- Operator information and guidance systems via display in the truck cabin and the Premium control panel
- Fully variable jacking for exact stabilizer positioning
- 1000mm stroke to compensate rough terrain
- Automatic set-up with adaptive levelling
- Counter slew-system permits extremely compact dimensions
- Rotation within mirror-width of the vehicle
- Time-saving outrigger control via automatic set-up from the ground
- Foldable rear crash protection increases slope angle
- Range optimisation through continuous processing of outrigger position, inclination and basket load
- Maximum speed, start and stop ramps individually adjustable
- Easy-to-use electronic emergency operation of all platform functions via display
- Diagnostic tools such as PALDIAG.CMI, Palfinger APP and QR-Code
- Available for two axle chassis with GVW from 15,5t upwards

WORKING DIAGRAMS



DIMENSIONS



KP-P370M1+EN

Units shown in the leaflet are partially optional equipped and do not always correspond to the standard version. Country-specific regulations must be observed. Dimensions may vary. Subject to technical changes, errors and translation mistakes.

TECHNICAL SPECIFICATIONS

Max. working height	37 m
Max. cage bottom height	35 m
Max. outreach to the side*	31.5 m
Max. outreach*	31.5 m
Rotation angle of turntable	500°
Rotation angle of cage	2 x 90°
Rotation angle of cage arm	185°
Max. cage load	500 kg
Size of cage	2.00 x 0.80 x 1.10 m
Permissible inclination of platform	2°
Height in transport position*	3.85 m
Width in transport position	2.50 m
Overall length*	8.35 m
Wheelbase*	3875 mm
Total weight*	ca. 15200 kg

*Depends on truck chassis