

Professional Coldwater Units Series KD

EHRLE KD Series





Hochdruck-Reinigungs-Systeme

High-Pressure-Cleaning-Systems

Coldwater High Pressure Cleaner, mobile - Model KD 823



Model KD 823 - Single Phase

Technical Data

Discharge Capacity	260 - 780l/h
Max. Pressure	150bar
Working Pressure	10 - 130bar
max. warm water inlet Temperature.	60°C
Voltage	AC 220-240V/50Hz
Connected Load	3,1kW / 16A

Description

Mobile coldwater Unit for professional use
Impact resistant Metal-Chassis for long durability
Unit fully protected by Steel-Frame
Triplex-Piston Pump with Brass Pump-Head, Ceramic Plungers and st.st. valves
Integral Leakage-Protection
Slow-running and air-cooled electric Motor with 1400 U/min
Infinitely variable pressure control via intelligent Unloader-Valve Technology
Chemical-Intake by low pressure Injector

Standard Scope of Delivery

- 10m professional High-Pressure Hose
- Regulator-Nozzle: Regulation on Nozzle from HP-Jet to Low-Pressure Chemical-Intake
- Storage Facility for HP-Hose, electr. Cable and chemical intake Hose
- Storage Facility for Trigger-Gun and Regulator-Nozzle
- **TSS-System:** Total-Start-Stop System with Off-Delay optional
- **STR-Version:** Professional Hose-Reel with st.st. Shaft and 15m Hose optional