

	Kränzle 115	Kränzle 125	Kränzle 135	Kränzle 145T	Kränzle 160TST
Operating pressure, fully adjustable	10 - 115 bar	10 - 125 bar	10 - 135 bar	10 - 125 bar	10 - 140 bar
Nozzle	25045	25045	25045	25045	25045
Max. permissible pressure	130 bar	140 bar	150 bar	145 bar	160 bar
Water flow	10,3 l/min at 1400 r.p.m.	10,5 l/min at 1400 r.p.m.	11 l/min at 1400 r.p.m.	10.5 l/min at 1400 r.p.m.	11 l/min at 1400 r.p.m.
Max. inlet water temperature	70° C	70° C	70° C	70° C	70° C
Max. suction height	2,5 m	2,5 m	2,5 m	2,5 m	2,5 m
Steel fabric high-pressure hose	10 m	10 m	10 m	15 m with hose reel	15 m with hose reel
Cleaning agent injector	yes	yes	yes	yes	yes
Supply voltage	230 V, 10 A, 50 Hz	230 V, 12 A, 50 Hz	230 V, 13,5 A, 50 Hz	230 V, 12,5 A, 50 Hz	230 V, 14,5 A, 50 Hz
Connection load: Input	P 1 - 2,4 kW	P 1 - 2,8 kW	P 1 - 3,1 kW	P 1 - 2,9 kW	P 1 - 3,4 kW
Connection load: Output	P 2 - 1,8 kW	P 2 - 2,0 kW	P 2 - 2,3 kW	P 2 - 2,2 kW	P 2 - 2,5 kW
Weight	32 kg	32 kg	32 kg	36 kg	36 kg
Dimensions in mm	350 x 330 x 900	350 x 330 x 900	350 x 330 x 900	350 x 330 x 900	350 x 330 x 900