

Die Grinder LXT®

DGD800

18V • 26 000 min⁻¹ • 8 mm

Long-framed tool for burr removal and grinding

A slimline, light die grinder with a 8 mm collet. This die grinder is suitable for small-scale grinding, including burr removal and finishing of metal doors. Achieves a high speed of 26 000 min⁻¹.



Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
No load speed	26000 min ⁻¹
Collet Capacity	6 mm
Wheel point max.	36 mm
Anti-Restart Function (NVR Switch)	✓
Vibration Level, Surface Grinding	5,5 m/s ²
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s ²
Sound Pressure Level (L _{pA})	72 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Product Dimensions (L x W x H):	402 x 82 x 118 mm
Tool weight with battery	1,7 - 2 kg

User benefits

- Slide switch with lock-on for continuous use
- LED light illuminates the work site
- Battery protection circuit protects against overloading, over-discharging and over-heating

Link to product - www.makita.dk



Related products

Optional AC

450128-8

Battery cover, LXT®, 14,4 – 18V



781039-9

Wrench 13



821550-0

Makpac case (2)



837806-1

MakPac (2) Inlay



BL1820B

Battery LXT® 2,0 Ah



BL1830B

Battery LXT® 3,0 Ah



BL1840B

Battery LXT® 4,0 Ah



BL1850B

Battery LXT® 5,0 Ah



BL1860B

Battery LXT® 6.0 Ah



Other

User manual

Parts drawing