


drives 25~50mm (1"~2")16ga. medium crown 11.1mm (7/16") staples

FEATURES

- Lightweight-only 2.3kg (4.8lbs)
- Powerful
- Rapid fire trigger valve

Fastest medium crown stapler in the market. It drives15 staples per second.



New durable easy jam clearance (Patent pending)



Adjustable depth control



TOOL SPECIFICATIONS


MODEL	TA551/16-11
WEIGHT	· 2.3kg(4.8lbs)
DIMENSIONS	275(H) × 82(W) × 356(L)mm 11-1/4" × 3-3/16" × 13-6/8"
LOAD CAPACITY	157 staples
OPERATING PRESSURE	5~7kg/cm*(Regulator) 70~100p.s.i.
AIR CONSUMPTION	0.832/cycle at 6 bar (90 p.s.i.) operating pressure
NOISE	A-weighted single-event sound power level LWA, 1s, d 91.92 dB A-weighted single-event emission sound pressure level at work station LpA, 1s, d 83.92 dB These values are determined and documented in accordance to CEN/TC 255 WG 1 N 45.3 E. (EN-standerd in preparation)
VIBRATION	Vibration characteristic value = 3.47m/s These values are determined and documented in accordance to ISO 8662-11



Maintenance free end cap filter (UK Patent 19539950) It prevents foreign substances from entering the tool. Internal

parts last longer and the inside of the tool is kept clean. The filter has a self-cleaning feature; foreign substances are ejected automatically from the tool when the air hose is disconnected.








- Comfortable rubber grip
- Durable alminum frame and cylinder cap

APPLICATIONS

- Sheathing
 Subflooring
 Forniture frames
 Pallets
 Crate and box assembly
- Vinyl Siding



The specifications and design of the products in this catalog will be subject to change without advance notice due to our continuous efforts to improve quality of our products



MAX CO.,LTD.

6-6,NIHONBASHI,HAKOZAKI-CHO,CHUO-KU,TOKYO,JAPAN PHONE: TOKYO 3669-8131 FAX:TOKYO 3669-7104 http://www.max-ltd.co.jp/int/

Distributor:

YOUNG BLACK LS, LTD THISTLE HOUSE, RADWAY ROAD BRITANNIA BUSINESS PARK SWINDON, SN3 4ND

TEL: 01793 838400 FAX: 01793 838401 E-mail: sales a youngblack.co.uk Web: www.youngblack.co.uk

