

SSDP30 30.0kVA / 24.0KW / 1 PHASE 230V

Standard Features : Electric push button start 1500 rpm Perkinswatercooled diesel engines, complete with high engine temperature shutdown, low oil pressure shutdown / Lockable control panel housing / Super silent close fitting skid mount acoustic cabinets with noise levels as low as 64dBA, complete with large access doors for ease of maintenance / Brushless maintenance free premier range Mecc Alte alternators complete with auto voltage regulation + or – 1.5% / Overload protection for each individual socket / Hard wire connection facility / RCD / ELCB / Bunded long range fuel tanks giving up to 48 hours running at 75% load / Three way valve for connection to bowser tank / Emergency Stop button and battery isolator switch for safety and security / Two wire remote start as standard (SSDP range only)

Specifications

OUTPUT:

30.0kVA / 24.0KW / 1 PHASE 230V

SOCKETS:

BS4343 industrial sockets -

1 x 230V 16A sockets

2 x 230V 32A sockets

1 x 230V 63A sockets

ENGINE:

PERKINS 1103A-33G

CYLINDERS:

3

FUEL TANK:

280 litres

RUN TIME:

48 hours @ 75% Load

NOISE LEVEL:

64dB (A) @ 7 metres. 89LWA

SIZE:

L2050x W1000 x H1490mm

WEIGHT:

1300kg (skid version).