

ADJUSTABLE MAGIC PLATFORM

PSM15



1. To commence deployment, place a foot on the bottom rung at the rear of the platform. Pull firmly down on the platform, until the deck is horizontal and the platform hooks are engaged.

2. Release the locking pins by disengaging from the lower locking position, the guardrails can now be slid to their full extent, with the locking pins firmly engaged at their upper position.



3. When the platform is in the required working position and the guardrails are in place, the stabilisers must be deployed. Move the stabiliser away from the stile. When the stabiliser will not move any further, pull the locking pin and push down on the lower arm, until the lower leg extends, locks and is resting securely on the ground.



4. To increase the height of the platform, support the inner ladder whilst releasing both side locks by pulling them outwards. Raise the inner ladder until the required platform height is achieved and replace both side locks, ensuring they are fully engaged.

5. When using the platform, the user should ensure the gate is fully closed.



NOTE When working against a wall, only the opposing stabiliser needs to be deployed

DO NOT

- EXCEED ONE PERSON ON PLATFORM
- EXCEED 110kg SAFE WORKING LOAD
- OVER-REACH
- MOVE WITH PERSONNEL ON PLATFORM

DO

- ONLY USE ON LEVEL SURFACES
- BEWARE OF OVERHEAD OBSTRUCTIONS
- RAISE STABILISERS BEFORE MOVING
- INSPECT PLATFORM FOR DAMAGE BEFORE USE